

Interactive Flat Panel

Android 13.0

EIBOARD Interacitve Flat Panel is an all-in-one smart board supporting Android and Windows operating system, widely used in education and business to enhance learning and collaboration, allowing for more dynamic and engaging presentations.

The popular sizes are 65" 75" 86". It adopts infrared touch and zero-gap bonding technology, enhance the writing accuracy and faster respond that make a better user experience.



Official Website



4K Original Panel

Zero-bonding makes writing more accurate, with A grade 4K touch panel.



Patent Design

Sliding lockable design for protecting front ports and buttons.



Wireless Screen Share

Wireless screen share connection up to 9 devices (IOS, Android, Windows).



OTA Update

Providing OTA firmware and software feature updates.



Apps Quick Access

Physical control of screen share, recording and eye protection.

Multi Users & Convenient Presentation

Smart writing interactive whiteboard supports 20/40 points finger touch, with easy annotation and gesture eraser.





Sliding Lockable Design

0.006 S Response speed



Gesture Eraser







In-built Google Search

Search and pull out relevant resources of writing contents, such as picture or text, in annotation software.





Dual Application Operation

Operate two applications to efficient courses and presentation.





Safety Lock

Support USB lock, touch lock, gesture lock, APP lock, screen lock management.



General Technical Parameters

| LCD Panel | Screen Size | 65" | 75" | 86" | | |
|---------------------------|---|-------------------------------------|----------------------------------|-------------------|--|--|
| | Screen Type | | DLED | | | |
| | Resolution | 3840(H)×2160(V) (UHD) | | | | |
| | Color | | 10 bit 1.07B | | | |
| | Active Size | 1428.48*803.52mm | 1649.66*927.93mm | 1895.04*1065.96mm | | |
| | Brightness | >350cd/m2 | | | | |
| | Contrast | 4000:1 (according to panel brand) | | | | |
| | Viewing Angle | 178° | | | | |
| | AG Glass | Tempered explosion-proof glass 4 mm | | | | |
| | Backlight Lifetime | >50000 hours | | | | |
| Electrical performance | Max Power | ≤250W | ≤300W | ≤400W | | |
| | Standby Power | | ≤0.5W | | | |
| | Voltage | 110-240V(AC), 50/60Hz | | | | |
| | Touch Technology | IR touch; 20 points; HIB Free drive | | | | |
| Touch | Touch Items | Finger, Pen, any opaque objects | | | | |
| Touch | Response Speed | | ≤ 6ms | | | |
| | Operation System | Suppo | rt Windows, Android, Mac OS, Lii | nux | | |
| System | Android 13.0 | | | | | |
| Processor | CPU: Cotex A55 * 4 Cores, 1.9GHz; GPU:Arm Mali-G52 MP2 | | | | | |
| Stroage | RAM 4/8GB, ROM 32/64/128G | | | | | |
| Network | LAN/WiFi 2.4G+5G, Bluetooth 5.0 | | | | | |
| Speakers | Power | 15W*2 / 8Ω | | | | |
| MA - uldin - | Working Temperature | perature 0°C ~ 40°C | | | | |
| Working Environment | Storage Temperature | - 20°C ~ 60°C | | | | |
| | Working Humidity | 10%-90% non-condensing | | | | |
| Accessories | Power cable*1 pcs; Remote controller*1 pcs; Touch pen*1pcs; QC & Warranty card*1 pcs; Wall mount brackets*1 pcs; | | | | | |
| | Optional items: Web camera, Mobile Stand, HDMI cable, Touch Cable, etc. | | | | | |
| I/O Interfaces | Input Ports: HDMI, LAN(RJ45), AV in(mini),USB 3.0, USB2.0, RS232 , Touch USB, OPS Slot Output Ports: SPDIF, AV, Earphone Front Ports: HDMI-in,Type-C, Touch USB, USB 3.0 | | | | | |
| Featured Apps | 4K Whiteboard, Screen Share, Split Screen, Browser, PlayStore, Child Lock, Annotation, FileTransfer, FileBrowser, Calender, Assitant, ScreenShot, Screen Record, Annotation, Vote | | | | | |

Options for Windows System

| OPS Type | OPS-C ; 80-Pin | | |
|------------------|--|--|--|
| Dimension | 195*180*42mm | | |
| CPU | Intel I3/i5/ i7 with 4th~12th or latest generation as option | | |
| Memory | 4G/8G/16G/32G DDR3/DDR4 as option | | |
| Storage | 128G/256 G /512 G SSD/1T as option | | |
| Operating System | Windows 10/11 Pro as option | | |

Product Dimension

| Items / Model No. | FC-65LED | FC-75LED | FC-86LED |
|-------------------|------------------------|-----------------|-----------------|
| Packing dimension | 1600*1014*200mm | 1822*1180*200mm | 2068*1370*200mm |
| Product dimension | 1485*893* 95 mm | 1707*1017*95mm | 1953*1168*95mm |
| Wall mount VESA | 500*400mm | 600*400mm | 750*400mm |
| Weight(N.W/G.W) | 41Kgs/52Kgs | 56Kgs/67Kgs | 71Kgs/82Kgs |