



NO.	Band	Frequency Range	Insertion Loss	Isolation	VSWR	Forward Power	Reverse Power	Working Temperature	Size(L x W x H)
1	UHF	350-370MHz	0.35dB	20dB	1.25:1	300W	300W	-20°C ~ +65°C	35*38*11mm
2	UHF	380-460MHz	0.5dB	18dB	1.3:1	300W	300W	-20°C ~ +65°C	35*38*11mm
3	UHF	400-470MHz	0.4dB	20dB	1.25:1	300W	300W	-30°C ~ +70°C	35*38*11mm
4	UHF	450-520MHz	0.4dB	20dB	1.25:1	300W	300W	-20°C ~ +65°C	35*38*11mm
5	UHF	600-800MHz	0.5dB	19dB	1.25:1	300W	300W	-20°C ~ +65°C	35*38*11mm
6	UHF	700-900MHz	0.4dB	20dB	1.25:1	300W	300W	-30°C ~ +70°C	35*38*11mm
7	L	1.0-1.1GHz	0.3dB	20dB	1.2:1	200W	200W	-40°C ~ +85°C	25.4*25.4*10mm
8	L	1.2-1.4GHz	0.3dB	20dB	1.2:1	200W	200W	-40°C ~ +85°C	25.4*25.4*10mm
9	L	1.4-1.6GHz	0.3dB	20dB	1.2:1	200W	200W	-40°C ~ +85°C	25.4*25.4*10mm

CHENGDU JINGXIN MICROWAVE TECHNOLOGY CO., LTD

Phone direct : +86 28 8502-6087

Email: sales@cdjx-mw.com <https://www.cdjx-mw.com>

Add: Youbo Centre, Wuhou District, Chengdu 610045, Sichuan, P.R.China

NO.	Band	Frequency Range	Insertion Loss	Isolation	VSWR	Forward Power	Reverse Power	Working Temperature	Size(L x W x H)
10	L	1.6-1.8GHz	0.3dB	20dB	1.2:1	200W	200W	-40°C ~ +85°C	25.4*25.4*10mm
11	L	1.8-2.0GHz	0.3dB	20dB	1.2:1	200W	200W	-40°C ~ +85°C	25.4*25.4*10mm
12	S	2.0-2.2GHz	0.3dB	20dB	1.25:1	200W	200W	-40°C ~ +85°C	25.4*25.4*10mm
13	S	2.2-2.4GHz	0.3dB	20dB	1.25:1	200W	200W	-40°C ~ +85°C	25.4*25.4*10mm
14	S	2.7-3.1GHz	0.3dB	20dB	1.25:1	200W	200W	-40°C ~ +85°C	25.4*25.4*10mm
15	S	3.0-3.6GHz	0.3dB	20dB	1.25:1	200W	200W	-40°C ~ +85°C	25.4*25.4*10mm
16	S	2.9-3.3GHz	0.3dB	20dB	1.25:1	60W	60W	-40°C ~ +85°C	12.7*12.7*8mm
17	C	4.4-5.0GHz	0.4dB	20dB	1.25:1	60W	60W	-40°C ~ +85°C	12.7*12.7*8mm
18	C	5.0-6.0GHz	0.4dB	18dB	1.25:1	60W	60W	-40°C ~ +85°C	12.7*12.7*8mm
19	C	6.5-7.0GHz	0.4dB	20dB	1.25:1	60W	60W	-40°C ~ +85°C	12.7*12.7*8mm
20	C	7.0-8.0GHz	0.4dB	20dB	1.25:1	60W	60W	-40°C ~ +85°C	12.7*12.7*8mm
21	X	8.0-9.0GHz	0.35dB	20dB	1.25:1	30W	30W	-40°C ~ +85°C	9*10*5.1mm
22	X	9.0-10.0GHz	0.35dB	20dB	1.25:1	30W	30W	-40°C ~ +85°C	9*10*5.1mm
23	X	10.0-11.0GHz	0.35dB	20dB	1.25:1	30W	30W	-40°C ~ +85°C	9*10*5.1mm
24	X	11.0-12.0GHz	0.35dB	20dB	1.25:1	30W	30W	-40°C ~ +85°C	9*10*5.1mm
25	X	8.0-12.0GHz	0.5dB	18dB	1.3:1	30W	30W	-40°C ~ +85°C	9*10*5.1mm

CHENGDU JINGXIN MICROWAVE TECHNOLOGY CO., LTD

Phone direct : +86 28 8502-6087

Email: sales@cdjx-mw.com <https://www.cdjx-mw.com>

Add: Youbo Centre, Wuhou District, Chengdu 610045, Sichuan, P.R.China

NO.	Band	Frequency Range	Insertion Loss	Isolation	VSWR	Forward Power	Reverse Power	Working Temperature	Size(L x W x H)
26	KU	13.0-15.0GHz	0.5dB	18dB	1.25:1	30W	30W	-40°C ~ +85°C	9*10*5.1mm
27	KU	14.0-16.0GHz	0.5dB	18dB	1.25:1	30W	30W	-40°C ~ +85°C	9*10*5.1mm
28	KU	16.0-18.0GHz	0.5dB	18dB	1.25:1	30W	30W	-40°C ~ +85°C	9*10*5.1mm
29	K	18.0-22.0GHz	0.6dB	18dB	1.3:1	30W	30W	-40°C ~ +85°C	13* 18*13.8mm
30	K	21.0-23.0GHz	0.5dB	20dB	1.25:1	30W	30W	-40°C ~ +85°C	13* 18*13.8mm
31	K	23.0-25.0GHz	0.5dB	20dB	1.25:1	30W	30W	-40°C ~ +85°C	13* 18*13.8mm
32	K	24.0-26.0GHz	0.5dB	20dB	1.25:1	30W	30W	-40°C ~ +85°C	13* 18*13.8mm
33	K	27.0-29.0GHz	0.5dB	20dB	1.25:1	30W	30W	-40°C ~ +85°C	13* 18*13.8mm
34	K	27.0-31.0GHz	1.1dB	16dB	1.4:1	30W	30W	-40°C ~ +85°C	13* 18*13.8mm
35	K	33.0-37.0GHz	1.2dB	16dB	1.4:1	30W	30W	-40°C ~ +85°C	13* 18*13.8mm
36	K	22.0-33.0GHz	1.7dB	13dB	1.7:1	10W	10W	-40°C ~ +80°C	13*16*12.6mm
37	Ka	26.5-40.0GHz	1.7dB	12dB	1.8:1	10W	10W	-40°C ~ +80°C	13*16*12.6mm

Note: As a professional manufacturer of RR components, OEM & ODM are available.