



NO.	Band	Frequency Range	Insertion Loss	Isolation	VSWR	Forward Power	Reverse Power	Working Temperature	Size(L x W x H)
1	UHF	350-370MHz	0.35dB	20dB	1.25:1	300W	30W	-20°C ~ +65°C	35*38*11mm
2	UHF	380-460MHz	0.5dB	18dB	1.3:1	300W	30W	-20°C ~ +65°C	35*38*11mm
3	UHF	400-470MHz	0.4dB	20dB	1.25:1	300W	30W	-30°C ~ +70°C	35*38*11mm
4	UHF	450-520MHz	0.4dB	20dB	1.25:1	300W	30W	-20°C ~ +65°C	35*38*11mm
5	UHF	600-800MHz	0.5dB	19dB	1.25:1	300W	30W	-20°C ~ +65°C	35*38*11mm
6	UHF	700-900MHz	0.4dB	20dB	1.25:1	300W	30W	-20°C ~ +65°C	35*38*11mm
7	UHF	350-370MHz	0.35dB	20dB	1.25:1	300W	100W	-20°C ~ +65°C	35*46*11mm

CHENGDU JINGXIN MICROWAVE TECHNOLOGY CO., LTD

Phone direct : +86 28 8502-6087

Email: sales@cdjx-mw.com <https://www.cdjx-mw.com>

Add: Youbo Centre, Wuhou District, Chengdu 610045, Sichuan, P.R.China

NO.	Band	Frequency Range	Insertion Loss	Isolation	VSWR	Forward Power	Reverse Power	Working Temperature	Size(L x W x H)
8	UHF	380-460MHz	0.5dB	18dB	1.3:1	300W	100W	-20°C ~ +65°C	35*46*11mm
9	UHF	400-470MHz	0.4dB	20dB	1.25:1	300W	100W	-30°C ~ +70°C	35*46*11mm
10	UHF	450-520MHz	0.4dB	20dB	1.25:1	300W	100W	-20°C ~ +65°C	35*46*11mm
11	UHF	600-800MHz	0.5dB	19dB	1.25:1	300W	100W	-20°C ~ +65°C	35*46*11mm
12	UHF	700-900MHz	0.4dB	20dB	1.25:1	300W	100W	-20°C ~ +65°C	35*46*11mm
13	L	1.0-1.1GHz	0.3dB	20dB	1.2:1	200W	30W	-40°C ~ +85°C	25.4*25.4*10mm
14	L	1.2-1.4GHz	0.3dB	20dB	1.2:1	200W	30W	-40°C ~ +85°C	25.4*25.4*10mm
15	L	1.4-1.6GHz	0.3dB	20dB	1.2:1	200W	30W	-40°C ~ +85°C	25.4*25.4*10mm
16	L	1.6-1.8GHz	0.3dB	20dB	1.2:1	200W	30W	-40°C ~ +85°C	25.4*25.4*10mm
17	L	1.8-2.0GHz	0.3dB	20dB	1.2:1	200W	30W	-40°C ~ +85°C	25.4*25.4*10mm
18	L	1.0-1.1GHz	0.3dB	20dB	1.2:1	200W	100W	-40°C ~ +85°C	25.4*31.7*10mm
19	L	1.2-1.4GHz	0.3dB	20dB	1.2:1	200W	100W	-40°C ~ +85°C	25.4*31.7*10mm
20	L	1.4-1.6GHz	0.3dB	20dB	1.2:1	200W	100W	-40°C ~ +85°C	25.4*31.7*10mm
21	L	1.6-1.8GHz	0.3dB	20dB	1.2:1	200W	100W	-40°C ~ +85°C	25.4*31.7*10mm
22	L	1.8-2.0GHz	0.3dB	20dB	1.2:1	200W	100W	-40°C ~ +85°C	25.4*31.7*10mm

CHENGDU JINGXIN MICROWAVE TECHNOLOGY CO., LTD

Phone direct : +86 28 8502-6087

Email: sales@cdjx-mw.com <https://www.cdjx-mw.com>

Add: Youbo Centre, Wuhou District, Chengdu 610045, Sichuan, P.R.China

NO.	Band	Frequency Range	Insertion Loss	Isolation	VSWR	Forward Power	Reverse Power	Working Temperature	Size(L x W x H)
23	S	2.0-2.2GHz	0.3dB	20dB	1.25:1	200W	30W	-40°C ~ +85°C	25.4*25.4*10mm
24	S	2.2-2.4GHz	0.3dB	20dB	1.25:1	200W	30W	-40°C ~ +85°C	25.4*25.4*10mm
25	S	2.7-3.1GHz	0.3dB	20dB	1.25:1	200W	30W	-40°C ~ +85°C	25.4*25.4*10mm
26	S	3.0-3.6GHz	0.3dB	20dB	1.25:1	200W	30W	-40°C ~ +85°C	25.4*25.4*10mm
27	S	2.0-2.2GHz	0.3dB	20dB	1.25:1	200W	100W	-40°C ~ +85°C	25.4*31.7*10mm
28	S	2.2-2.4GHz	0.3dB	20dB	1.25:1	200W	100W	-40°C ~ +85°C	25.4*31.7*10mm
29	S	2.7-3.1GHz	0.3dB	20dB	1.25:1	200W	100W	-40°C ~ +85°C	25.4*31.7*10mm
30	S	3.0-3.6GHz	0.3dB	20dB	1.25:1	200W	100W	-40°C ~ +85°C	25.4*31.7*10mm
31	C	4.4-5.0GHz	0.4dB	20dB	1.25:1	60W	20W	-40°C ~ +85°C	12.7*12.7*8mm
32	C	5.0-6.0GHz	0.4dB	18dB	1.25:1	60W	20W	-40°C ~ +85°C	12.7*12.7*8mm
33	C	6.5-7.0GHz	0.4dB	20dB	1.25:1	60W	20W	-40°C ~ +85°C	12.7*12.7*8mm
34	C	7.0-8.0GHz	0.4dB	20dB	1.25:1	60W	20W	-40°C ~ +85°C	12.7*12.7*8mm
35	C	4.0-8.0GHz	0.7dB	16dB	1.5:1	100W	75W	-40°C ~ +85°C	16*23*6.4mm
36	C	3.8-8.0GHz	0.9dB	14dB	1.7:1	100W	75W	-40°C ~ +85°C	16*23*6.4mm
37	C	4.4-5.0GHz	0.4dB	20dB	1.25:1	75W	100W	-40°C ~ +85°C	12.7*19.1*8mm

CHENGDU JINGXIN MICROWAVE TECHNOLOGY CO., LTD

Phone direct : +86 28 8502-6087

Email: sales@cdjx-mw.com <https://www.cdjx-mw.com>

Add: Youbo Centre, Wuhou District, Chengdu 610045, Sichuan, P.R.China

NO.	Band	Frequency Range	Insertion Loss	Isolation	VSWR	Forward Power	Reverse Power	Working Temperature	Size(L x W x H)
38	C	5.0-6.0GHz	0.4dB	18dB	1.25:1	75W	100W	-40°C ~ +85°C	12.7*19.1*8mm
39	C	6.5-7.0GHz	0.4dB	20dB	1.25:1	75W	100W	-40°C ~ +85°C	12.7*19.1*8mm
40	C	7.0-8.0GHz	0.4dB	20dB	1.25:1	75W	100W	-40°C ~ +85°C	12.7*19.1*8mm
41	X	8.0-9.0GHz	0.35dB	20dB	1.25:1	30W	10W	-40°C ~ +85°C	9*10*5.1mm
42	X	9.0-10.0GHz	0.35dB	20dB	1.25:1	30W	10W	-40°C ~ +85°C	9*10*5.1mm
43	X	10.0-11.0GHz	0.35dB	20dB	1.25:1	30W	10W	-40°C ~ +85°C	9*10*5.1mm
44	X	11.0-12.0GHz	0.35dB	20dB	1.25:1	30W	10W	-40°C ~ +85°C	9*10*5.1mm
45	X	8.0-12.0GHz	0.5dB	18dB	1.3:1	30W	10W	-40°C ~ +85°C	9*10*5.1mm
46	X	8.0-9.0GHz	0.35dB	20dB	1.25:1	30W	10W	-40°C ~ +85°C	9*14*5.1mm
47	X	9.0-10.0GHz	0.35dB	20dB	1.25:1	30W	10W	-40°C ~ +85°C	9*14*5.1mm
48	X	10.0-11.0GHz	0.35dB	20dB	1.25:1	30W	10W	-40°C ~ +85°C	9*14*5.1mm
49	X	11.0-12.0GHz	0.35dB	20dB	1.25:1	30W	10W	-40°C ~ +85°C	9*14*5.1mm
50	KU	13.0-15.0GHz	0.5dB	18dB	1.25:1	30W	10W	-40°C ~ +85°C	9*10*5.1mm
51	KU	14.0-16.0GHz	0.5dB	18dB	1.25:1	30W	10W	-40°C ~ +85°C	9*10*5.1mm
52	KU	16.0-18.0GHz	0.5dB	18dB	1.25:1	30W	10W	-40°C ~ +85°C	9*10*5.1mm

CHENGDU JINGXIN MICROWAVE TECHNOLOGY CO., LTD

Phone direct : +86 28 8502-6087

Email: sales@cdjx-mw.com <https://www.cdjx-mw.com>

Add: Youbo Centre, Wuhou District, Chengdu 610045, Sichuan, P.R.China

NO.	Band	Frequency Range	Insertion Loss	Isolation	VSWR	Forward Power	Reverse Power	Working Temperature	Size(L x W x H)
53	KU	13.0-15.0GHz	0.5dB	18dB	1.25:1	30W	10W	-40°C ~ +85°C	9*14*5.1mm
54	KU	14.0-16.0GHz	0.5dB	18dB	1.25:1	30W	10W	-40°C ~ +85°C	9*14*5.1mm
55	KU	16.0-18.0GHz	0.5dB	18dB	1.25:1	30W	10W	-40°C ~ +85°C	9*14*5.1mm
56	K	18.0-22.0GHz	0.6dB	18dB	1.3:1	30W	5W	-40°C ~ +85°C	13* 18*13.8mm
57	K	21.0-23.0GHz	0.5dB	20dB	1.25:1	30W	5W	-40°C ~ +85°C	13* 18*13.8mm
58	K	23.0-25.0GHz	0.5dB	20dB	1.25:1	30W	5W	-40°C ~ +85°C	13* 18*13.8mm
59	K	24.0-26.0GHz	0.5dB	20dB	1.25:1	30W	5W	-40°C ~ +85°C	13* 18*13.8mm
60	K	25.0-27.0GHz	0.5dB	20dB	1.25:1	30W	5W	-40°C ~ +85°C	13* 18*13.8mm
61	Ka	26.5-40.0GHz	1.7dB	12dB	1.8:1	10W	2W	-40°C ~ +80°C	13*16*12.6mm

Note: As a professional manufacturer of RR components, OEM & ODM are available.

CHENGDU JINGXIN MICROWAVE TECHNOLOGY CO., LTD

Phone direct : +86 28 8502-6087

Email: sales@cdjx-mw.com <https://www.cdjx-mw.com>

Add: Youbo Centre, Wuhou District, Chengdu 610045, Sichuan, P.R.China